

WHAT IS CLAIMED IS:

Sub
B8
1. A relaying apparatus for use in a network system, which network system is formed with a plurality of client terminals and server terminals providing services to those client
5 terminals via a network, comprising:

a plurality of route load measuring units each provided in the vicinity of each of said server terminals and each measures a respective load in the route up to one client terminal having issued a request for service out of said client
10 terminals; and

a selecting unit which selects one server terminal out of said server terminals as a destination of the request for service from said one client terminal based on the route load measured by said route load measuring units.

15
Sub
a12
2. The relaying apparatus for used in a network system according to Claim 1 further comprises a storing unit which store a route load measured at a pre-specified time interval by each of said route load measuring units up to said one client
20 terminal; and

when a request for service is received from said one client terminal, said selecting unit selects said one server terminal out of said server terminals as a destination of the request for service from said one client terminal based on the
25 route load stored in the storing unit.

3. The relaying apparatus for use in a network system according to Claim 2; wherein each of said route load measuring units monitors the operating states of respective server terminal; and

5 when a request for service is received from said one client terminal, said selecting unit selects one server terminal out of said server terminals as a destination of the request for service from said one client terminal based on the route load and the operating states monitored by said load measuring units.

4. A relaying apparatus for use in a network system, which network system is formed with a plurality of client terminals and server terminals divided into several groups providing services to those client terminals via a network, comprising:

15 a plurality of route load measuring units each provided with respect to each of the groups and each measures a respective load in the route up to one client terminal having issued a request for service out of said client terminals; and

20 a selecting unit which selects one route load measuring units out of said route load measuring units as a primary destination of the request for service from said one client terminal based on the route load measured by said route load measuring units; wherein said one route load measuring unit
25 selects one server terminal out of the several server terminals

in the group as a secondary destination of the request for service from said one client terminal.

B1
cont

5. The relaying apparatus for use in a network system according to Claim 4; wherein each of said route load measuring units monitors the operating states of respective server terminal; and said one route load measuring unit select one server terminal out of the several server terminals in the group based on the operating states when selecting a secondary destination of the request for service from said one client terminal.

6. A relaying apparatus for use in a network system, which network system is formed with a plurality of client terminals and server terminals divided into several groups providing services to those client terminals via a network, comprising:

a plurality of route load measuring units each provided with respect to each of the groups, each measures a respective load in the route up to one client terminal having issued a request for service out of said client terminals and monitors the operating state of said server terminals in each group; and

a selecting unit which selects one route load measuring units out of said route load measuring units as a primary destination of the request for service from said one client terminal based on the route load measured and operating state

monitored by said route load measuring units; wherein said one route load measuring unit selects based on the operating state one server terminal out of the several server terminals in the group as a secondary destination of the request for service from

5 said one client terminal.

B1

Ad
B7

045322 120790